

Product data sheet Characteristics

4RCBE232/30S

Residual current breaker with overcurrent protection (RCBO), MAX4, 1P + N, 32 A, C curve, 6000 A, 240 V, 30 mA, A type





Range MAX4 Product or component Residual current breaker with overcurrent protection (RCBO) type Product brand Clipsal Device application Distribution Poles description 1P + N Left Neutral position Number of modules 1

Number of protected poles [In] rated current 32 A

Main

Network type AC Trip unit technology Thermal-magnetic

Earth-leakage sensitivity 30 mA

Earth-leakage Type A protection class

6000 A

Complementary

Complementary	
[Ue] rated operational voltage	240 V AC
Local signalling	ON/OFF indication
Mounting mode	Clip-on
Mounting support	DIN rail

Curve code

Breaking capacity

Environment

IP degree of protection	IP20 conforming to IEC 60529
	IP40 (modular enclosure) conforming to IEC 60529

Packing Units

Package 1 Weight	0.132 kg	
Package 1 Height	0.020 mm	
Package 1 width	0.075 mm	
Package 1 Length	0.100 mm	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	€ Yes	

China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Life Is On