

Product data sheet Characteristics

4CB110/6

Miniature circuit breaker, MAX4, 1P, 10 A, C curve, 6000 A, 240 V



Main

Product brand	Clipsal

Complementary

Complementary		
Curve code	С	
Number of poles	1	
[In] rated current	10 A	
Number of modules	1	
[Ue] rated operational voltage	240 V	
Breaking capacity	6 kA conforming to EN 60898	
Network type	AC	
Network frequency	50/60 Hz	
Mechanical durability	20000 cycles	
Electrical durability	20000 cycles	
Connections - terminals	Screw terminal for 1 cable(s) 0.7516 mm² rigid Screw terminal for 1 cable(s) 0.3310 mm² flexible Screw terminal for 1 cable(s) 0.3310 mm² flexible with ferrule	
Wire stripping length	13 mm	
Tightening torque	2 N.m	

Environment

IP degree of protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529	
Ambient air temperature for operation	-2570 °C	
Ambient air temperature for storage	-4070 °C	
Standards	AS/NZS 60898	
Tropicalisation	2	
Relative humidity	95 % at 55 °C	
Height	81 mm	
Width	18 mm	
Depth	78.5 mm	
Net weight	115 g	

Packing Units

Package 1 Weight	103.000 g	
Package 1 Height	18.000 mm	
Package 1 width	74.000 mm	
Package 1 Length	85.000 mm	

Offer Sustainability

EU RoHS Directive	Compliant EEEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₽¥Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure		

Life Is On | IICLIPSAL